

2021 SOUTHERN OUTLAW FWD RULES

COMPETING MODELS

1. Any Four Cylinder Front Wheel Drive car, except the following: No Convertibles, Vans, No Turbo or Super Charged Engines.
2. **Must have wrecker hookups under the hood and inside trunk area to safely lift car in case of an accident**

FANS AND RADIATORS

1. Electric fans may be used
2. Aftermarket radiator may be used
3. No antifreeze permitted

STEERING WHEELS

1. Locking mechanism must be removed
2. All steering wheels must be magnetic
3. All steering wheels must be equipped with a quick release coupling

WHEELS AND TIRES

1. Aftermarket steel wheels permitted
2. Race tires (required by track)

BRAKES

1. Rotors and drums must be magnetic steel.
2. All brakes must be in working order.

FUEL SYSTEM

1. Fuel cells are mandatory unless using Fuel injection, Fuel injected cars may use the stock fuel tank.
2. Fuel injected cars may use the stock gas tank and must run less than half capacity. A fuel line for these cars cannot run through the driver's compartment.
3. Fuel cells must be mounted and the center of the frame rails as far forward as possible. May be open in the bed area
4. A fuel cell protector bar height minimum of 1½ inches in diameter and a minimum wall thickness of 0.083 inches magnetic steel tubing must be used.
5. The bar must extend below the frames section behind a fuel cell or the fuel tank.

BODIES

1. Hoods must have a minimum of (2) hood pins on the hood
2. Headlights, taillights and parking lenses must be removed and openings filled with a sheet metal.
3. Inner door panels may be removed.



2021 SOUTHERN OUTLAW FWD RULES

4. All glass must be removed. LEXAN windshield and rear glass must be installed and secured with support straps, no pop rivets.
5. The battery must be mounted out of the driver's area in a Steel Container or battery box. The trunk area is the recommended location

SAFETY

ROLL BARS

1. Four (4) point cages with curved door bars required.
2. Roll bars must be welded and made of a minimum wall thickness of .090 seamless tubing.
3. Roll bars must be at least 1 ½ inch OD.
4. Roll bar may be extended through the firewall and loop around radiator.
5. Roll bars may be extended to the rear deck also.
6. Fuel cell protector must be installed behind fuel cell.
7. Right side cage must have a minimum of 3 bars in the door area.
8. Drivers door roll bars should have intrusion plates welded to the outside a minimum of 1/8 inch plates.
9. Refer to the Whelen All American Series rulebook for cage construction guidelines.
10. The tech person will have the authority to disallow any car with compromised structural integrity or protruding parts that may be dangerous to a competitor.

SEAT BELTS

1. Seat belts must be a 5 point harness type
2. Seat belts must be in date in accordance with the manufactures date on the label. The belts may be recertified
3. Seat belts must not be mounted to the floor pan
4. Seat belts must not cross areas that may cut the belts i.e. not across sheet metal attached to a roll bar
5. Seat belts must be replaced if they are worn or the edges are frayed

SEATS

1. Aluminum factory made racing seats required.
2. Absolutely no homemade seats
3. Seats must be mounted in a manner acceptable to OCS Officials
4. Seats may not be mounted to the floor pan

WINDOW NETS

1. An OCS approved window net must be installed on the driver's side window
2. Window net must release from the top and drop down
3. Window net bars must be substantial enough to contain the driver's arms in the event of a roll over

FIRE EXTINGUISHER

1. All cars must have an onboard fire extinguisher
2. Extinguisher must be mounted so the charge gage can be checked by OCS Officials



3. Out of date fire extinguishers are not allowed

SPOTTERS

1. All cars must have a spotter in the spotter stand. It is also recommended that all crews should monitor OCS race control.

FINAL NOTE: Orange County Speedway ultimately has the final decision on all participants and decisions. Please read all the rules and build your car accordingly.

OCS